



Datasheet



Document Manager

- Compact multifunctional A3 colour systems – ideal for up-and-coming businesses
- Excellent colour quality and flexible finishing options which meet your needs
- Individual templates on LCD and in printer driver to allow for efficient and productive workflows
- Environment friendly thanks to improved toner technology

e-STUDIO2050c
e-STUDIO2550c



SAP® Printer Vendor Solution



Networking Documents.

TOSHIBA
 Leading Innovation >>>



e-STUDIO2050c
e-STUDIO2550c



<p>General</p>	<p>Print & Copy Speed Colour: 20/25 ppm (A4), 10/12 ppm (A3) B&W: 20/25 ppm (A4), 10/12 ppm (A3)</p> <p>Warm-up Time Approx. 15 seconds from low power mode</p> <p>Paper Size & Weight Cassettes: A5R-A3, 60-163 g/m² Large Capacity Feeder¹⁾: A4, 60-163 g/m² Bypass: 100 x 148 mm-A3, 60-209 g/m²</p> <p>Paper Capacity 250 sheets (Cassettes), 100 sheets (Bypass) Maximum: 2,900 sheets</p> <p>Automatic Duplex A5R-A3, 60-163 g/m²</p> <p>Inner Output Tray 550-sheet capacity</p> <p>Controller Type Toshiba e-BRIDGE</p> <p>Control Panel Tilttable with 9" (22.8 cm) colour LCD touch screen</p> <p>Memory 8 GB SSD, 2 GB RAM, 160 GB Toshiba Secure HDD^{1) 2)}</p> <p>Interface 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g)</p> <p>Dimensions & Weight 575 x 590 x 662 mm (W x D x H), ~ 57 kg</p>
<p>Print</p>	<p>Resolution Max. 600 x 600 dpi, 5 bit per colour channel Max. 600 x 1,200 dpi, 1 bit per colour channel</p> <p>Page Description Languages XPS, PCL6 and PostScript 3 compatible</p> <p>Supported Systems Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400</p> <p>Colour Modes Auto-Colour (ACS), Colour, Twin Colour, B&W</p> <p>Colour Settings Brightness, Saturation, Contrast, Colour Balance, ICC profiles management</p> <p>Print Functions Universal Driver, Driver templates, Driver plug-ins, Private/Hold print³⁾, Print from USB, Tandem printing, etc.</p>
<p>Scan</p>	<p>Resolution Max. 600 x 600 dpi</p> <p>Scan Speed Colour & B&W: up to 50 ipm (300 dpi)</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W</p> <p>File Formats JPEG, Multi/Single Page TIFF/XPS³⁾/PDF, Secure PDF, Slim PDF, Searchable PDF¹⁾ (and other formats like DOC, XLS, RTF, TXT, PDF/A)¹⁾</p> <p>Scan Functions WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local³⁾), Meta Scan¹⁾, Scan to Box (e-Filing³⁾), TWAIN 1.7/1.8/1.9³⁾, Remote TWAIN</p>
<p>Copy</p>	<p>Resolution Scan: 600 x 600 dpi, 10 bit per colour channel Print: 600 x 600 dpi, 5 bit per colour channel</p> <p>First Copy Output Time Colour: Approx. 10.3 seconds B&W: Approx. 8.2 seconds</p> <p>Zoom 25-400% (platen), 25-200% (RADF)¹⁾</p> <p>Copy Modes Text, Text/Photo, Photo, Printed Image, Map</p> <p>Colour Modes Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W</p> <p>Colour Settings Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment</p>
<p>Fax¹⁾</p>	<p>Communication Super G3, G3 - (opt. 2nd line), Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p> <p>Fax Memory 100 MB (SSD)/1 GB (HDD)¹⁾ Transmission/Reception</p> <p>Network-Fax Driver for Windows 7/Vista/XP/Server 2008 R2, etc.</p> <p>Incoming Fax Routing To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing³⁾</p>
<p>System & Security</p>	<p>Device Management e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration</p> <p>System Features e-Filing³⁾ document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 60/12,060³⁾ One-touch Templates for storage of personalised settings or workflows, RIP-while-Print³⁾, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip³⁾</p> <p>Accounting & Security Role Based Access, LDAP support, 50/1,000³⁾ department codes & 100/10,000³⁾ user codes, card reader¹⁾, Quota management, standard data encryption with Toshiba Secure HDD³⁾, Data Overwrite Enabler^{1) 3)}, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant^{1) 3)}, Scan to Secure PDF</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.</p>

<p>OPTIONS</p>
<p>PLATEN COVER – KA-1640PC</p>
<p>RADF – MR-3024 100-sheet capacity, A5R-A3, 35-157 g/m²</p>
<p>JOB SEPARATOR – MJ-5004 2 inner trays, 150- and 250-sheet capacity</p>
<p>INNER FINISHER – MJ-1036 2 trays, 600-sheet capacity 50-sheet multi-position stapling 482 x 508 x 232 mm (W x D x H), ~ 15.3 kg</p>
<p>SADDLE-STITCH FINISHER – MJ-1037 1 tray, 1,000-sheet capacity 50-sheet multi-position stapling Saddle-stitched booklets of up to 60 pages 500 x 642 x 961 mm (W x D x H), ~ 37 kg</p>
<p>HOLE PUNCH UNIT – MJ-6007/MJ-6008 Options for Finisher MJ-1036/MJ-1037 Available in 2 holes (E), 4 holes (F/S) 126 x 464 x 174 mm (W x D x H), ~ 3.3 kg 120 x 597 x 245 mm (W x D x H), ~ 3.4 kg</p>
<p>CASSETTE – MY-1040 550-sheet capacity, A5R-A3, 60-163 g/m² 575 x 583 x 163 mm (W x D x H), ~ 9.5 kg</p>
<p>PAPER FEED PEDESTAL – KD-1032 550 sheets (1 drawer), A5R-A3, 60-163 g/m² 668 x 701 x 292 mm (W x D x H), ~ 16.3 kg</p>
<p>LARGE CAPACITY FEEDER – KD-1031A4 2,000-sheet capacity, A4, 64-105 g/m² 668 x 735 x 292 mm (W x D x H), ~ 26 kg</p>
<p>OTHER OPTIONS</p> <p>DESK – MH-2050</p> <p>PAPER FEED CONTROLLER – GH-1080</p> <p>DRAWER MODULE – MY-1039</p> <p>TOSHIBA SECURE HDD 160 GB²⁾ – GE-1220</p> <p>FAX BOARD – GD-1320EU</p> <p>FRONT USB KIT – GR-1140</p> <p>WORK TRAY – KK-4550</p> <p>DATA OVERWRITE ENABLER – GP-1070³⁾</p> <p>e-BRIDGE ID-GATE – KP-2004/5, TWN3XX</p> <p>WIRELESS LAN MODULE – GN-1060</p> <p>META SCAN ENABLER – GS-1010</p> <p>IPsec ENABLER – GP-1080</p> <p>UNICODE FONT ENABLER – GS-1007³⁾</p> <p>e-BRIDGE Re-Rite – GB-1280</p> <p>DAMP HEATER KIT – MF-2050CE</p> <p>ACCESSIBILITY ARM – KK-2550</p> <p>¹⁾ Optional ²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed. ³⁾ Requires Toshiba Secure HDD</p>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks in their respective markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2012 TOSHIBA TEC. DS2550cGBIDD1207

**TOSHIBA TEC GERMANY
IMAGING SYSTEMS GMBH**
CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
Leading Innovation >>>