



Document Manager

- Efficient, fast and easy office document communication for departmental workgroups.
- Latest Toshiba e-BRIDGE technology at 25/30 pages per minute with reliable and exceptional ease-of-use in B&W print, copy, fax, and Colour Scan.
- Reduced energy consumption in sleep mode – only 1 watt power is used.
- Efficient internal toner recycling system saves cost and resources.

e-STUDIO255
e-STUDIO305





e-STUDIO255
e-STUDIO305



<p>General</p>	<p>Print & Copy Speed 25/30 ppm (A4), 16/16 ppm (A3)</p> <p>Warm-up Time Approx. 20 seconds</p> <p>Paper Size & Weight Cassettes: A5R-A3, 64-105 g/m² Bypass: A5R-A3, 52-209 g/m²</p> <p>Paper Capacity 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Maximum: 3,200 sheets</p> <p>Automatic Duplex A5R-A3, 64-105 g/m²</p> <p>Inner Output Tray 550-sheet capacity</p> <p>Controller Type Toshiba e-BRIDGE</p> <p>Control Panel Tilttable with 8.5" colour LCD touch screen</p> <p>Memory 60 GB HDD, 1 GB RAM</p> <p>Interface 10/100 BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g), Bluetooth¹⁾</p> <p>Dimensions & Weight 575 x 586 x 756 mm (W x D x H), ~ 57 kg</p>
<p>Print</p>	<p>Resolution Max. 2,400 x 600 dpi with smoothing</p> <p>Page Description Languages XPS, PCL6 and PostScript 3 compatible</p> <p>Supported Systems Windows 2000, Windows XP/Server 2003/Server 2008/Vista (32/64 bit), Mac OS X, Linux/UNIX, Novel NetWare, Citrix, SAP, AS/400</p>
<p>Scan</p>	<p>Resolution Max. 600 x 600 dpi, 8 bit per colour channel</p> <p>Scan Speed Colour & B&W: Up to 43/57 ppm (300 dpi)</p> <p>Document Feeder¹⁾ Max. 100 sheets, A5R-A3, 35-157 g/m²</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W</p> <p>File Formats JPEG, Multi/Single Page TIFF, Multi/Single Page XPS, Multi/Single Page PDF, Secure PDF, Slim PDF (high compression), Searchable PDF¹⁾ (and other editable formats like DOC, XLS, RTF, TXT)¹⁾</p> <p>Scan Functions WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, IPX/SPX, local), Meta Scan¹⁾, Scan to Box (e-Filing), TWIN1.7/1.8/1.9</p>
<p>Copy</p>	<p>Resolution Scan: 600 x 600 dpi</p> <p>First Copy Output Time Print: 2,400 x 600 dpi with smoothing</p> <p>Zoom Approx. 4.7 seconds</p> <p>Copy Modes 25-400% (platen), 25-200% (RADF¹⁾) Text, Text/Photo, Photo, Colour Document, Custom</p>
<p>Fax¹⁾</p>	<p>Communication Super G3, G3 - (opt. 2nd line), Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p> <p>Fax Memory Transmission: 500 MB (HDD) Reception: 200 MB (HDD)</p> <p>Network-Fax Driver for Windows 2000, Windows XP/Server 2003/Server 2008/Vista (32/64 bit)</p> <p>Incoming Fax Routing To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing</p>
<p>System & Security</p>	<p>Device Management e-BRIDGE Fleet Management Software¹⁾, TopAccess for remote administration and configuration</p> <p>System Features e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Print from USB, RIP while Print, e-BRIDGE Open Platform¹⁾</p> <p>Accounting & Security Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader¹⁾, private/hold print, standard data encryption, Data Overwrite Enabler¹⁾, IP and MAC address filter, port filter, support of SSL and IPSec¹⁾ protocols, IEEE802.1x support, Scan to Secure PDF</p>

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.

OPTIONS

RADF – MR-3021

100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR – MJ-5004

2 inner trays, 150- and 250-sheet capacity

OFFSET TRAY – MJ-5005

250-sheet capacity

HANGING FINISHER – MJ-1031

1 tray, 1,000-sheet capacity
50-sheet single position stapling
A5R-A3, 64-105 g/m² (stapling mode)
411 x 595 x 383 mm (W x D x H), ~ 12 kg

SADDLE-STITCH FINISHER – MJ-1025

1 tray, 1,000-sheet capacity
50-sheet multi-position stapling
Saddle-stitched booklets of up to 40 pages
A5R-A3, 64-90 g/m² (stapling mode)
538 x 603 x 1,011 mm (W x D x H), ~ 38 kg

HOLE PUNCH UNIT – MJ-6005

Option for Finisher MJ-1025
Available in 2 holes (E), 4 holes (F), 4 holes (S)
90 x 560 x 170 mm (W x D x H), ~ 4 kg

PAPER FEED PEDESTAL – KD-1025

550 sheets (1 cassette), A5R-A3, 64-105 g/m²
668 x 701 x 291.5 mm (W x D x H), ~ 21 kg

LARGE CAPACITY FEEDER – KD-1026A4

2,000-sheet capacity, A4, 64-105 g/m²
668 x 737 x 291.5 mm (W x D x H), ~ 25 kg

e-BRIDGE RE-RITE – GB-1280

Advanced scan function for editable and searchable document formats creation

OTHER OPTIONS

- DESK – MH-2520
- CASSETTE – MY-1033
- FAX BOARD – GD-1250EU
- DATA OVERWRITE ENABLER – GP-1070
- e-BRIDGE ID-GATE – KP-2004/KP-2005
- WIRELESS LAN MODULE – GN-1050
- BLUETOOTH MODULE – GN-2010
- META SCAN ENABLER – GS-1010
- WEB-SERVICES ENABLER – GS-1020
- ACCESSIBILITY ARM – KK-2550
- IPSec ENABLER – GP-1080

¹⁾ Optional



**TOSHIBA TEC GERMANY
IMAGING SYSTEMS GMBH**

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
Leading Innovation >>>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2009 Toshiba TEC. DS305GBNEID0904