



Document Manager

- Multifunctional A3 system for excellent document output quality.
- Sophisticated, yet easy to use technology for maximised productivity.
- Extensive range of optional finishing features and software solutions.
- Discover state-of-the-art data security, featuring the Toshiba Secure HDD.
- Designed to meet the highest environmental standards.



e-STUDIO257
e-STUDIO307



SAP® Printer Vendor Solution





e.STUDIO257
e.STUDIO307



General	<p>Print & Copy Speed 25/30 ppm (A4), 16/16 ppm (A3) Warm-up Time Approx. 20 seconds Paper Size & Weight Cassettes: A5R-A3, 64-105 g/m² Large Capacity Feeder¹⁾: A4, 64-105 g/m² By-pass: A5R-A3, 52-209 g/m² Paper Capacity 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Max. 3,200 sheets Automatic Duplex A5R-A3, 64-105 g/m² Controller Type Toshiba e-BRIDGE Control Panel 9" (22.8 cm) colour touch panel LCD Memory Toshiba Secure HDD 320 GB²⁾ / 2 GB RAM Interface 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g/n) Dimensions (W x D x H) 575 x 586 x 756 mm Weight ~ 55 kg</p>
Print	<p>Resolution 600 x 600 dpi 2,400 x 600 dpi with smoothing Page Description Languages XPS, PCL6 and PostScript 3 compatible Supported Systems Windows 8/7/Vista/Server 2008/Server 2003 (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64 bit), Mac OS 10.4.11 - 10.9, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400 Print Functions Universal Driver, Driver templates, Driver plug-ins¹⁾, Hold Print, Print from USB, Tandem printing, AirPrint</p>
Scan	<p>Resolution Max. 600 x 600 dpi, 8 bit per colour channel Scan Speed Colour/B&W: 43/57 ipm (300 dpi) Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W File Formats JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, Searchable PDF¹⁾ (and other formats like DOCX, XLSX, RTF, TXT, PDF/A)¹⁾ Scan Functions Web Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan¹⁾, Scan to Box (e-Filing), WIA, TWAIN</p>
Copy	<p>Resolution Scan: 600 x 600 dpi Print: 2,400 x 600 dpi with smoothing First Copy Output Time Approx. 4.7 seconds Zoom 25-400% (platen), 25-200% (RADF)¹⁾ Copy Modes Text, Text/Photo, Photo, Colour Document, Custom</p>
Fax¹⁾	<p>Communication Super G3, G3 - (opt. 2nd line), Internet Fax T.37 Transmission Speed Approx. 3 seconds per page Compression JBIG, MMR, MR, MH Fax Memory 1 GB (HDD) Transmission/Reception Network-Fax Driver for Windows 8/7/Vista (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64 bit) Incoming Fax Routing To shared folder (SMB, FTP, IPX/SPX), E-Mail, e-Filing</p>
System & Security	<p>Device Management e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration System Features e-Filing document server for secure storage, document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip Accounting & Security Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader¹⁾, private print, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler¹⁾, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant¹⁾, Scan to Secure PDF</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.</p>

OPTIONS

RADF – MR-3028
100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR TRAY – MJ-5004
2 inner trays, 150- and 250-sheet capacity

OFFSET TRAY – MJ-5005
250-sheet capacity

INNER FINISHER – MJ-1032N
2 trays, 600-sheet capacity
50-sheet multi-position stapling
482 x 508 x 232 mm (W x D x H), ~ 13 kg

SADDLE-STITCH FINISHER – MJ-1033
1 tray, 1,000-sheet capacity
50-sheet multi-position stapling
Saddle-stitched booklets of up to 60 pages
409 x 624 x 961 mm (W x D x H), ~ 39 kg

HOLE PUNCH UNIT – MJ-6007/MJ-6008
Options for Finisher MJ-1032N/MJ-1033
Available in 2-holes (E), 4-holes (F/S)
120 x 245 x 597 mm (W x D x H), ~ 3.3 kg
126 x 463 x 174 mm (W x D x H), ~ 3.4 kg

PAPER FEED PEDESTAL – KD-1025
550-sheet (1 drawer), A5R-A3, 64-105 g/m²
668 x 701 x 291.5 mm (W x D x H), ~ 21 kg

LARGE CAPACITY FEEDER – KD-1026A4
2,000-sheet capacity, A4, 64-105 g/m²
668 x 737 x 292 mm (W x D x H), ~ 26 kg

OTHER OPTIONS

- DESK – MH-2520
- DRAWER MODULE – MY-1033
- HDD 320 GB²⁾ (FIPS 140-2 STD) – GE-1230
- FAX BOARD – GD-1350EU
- WIRELESS LAN MODULE – GN-1060
- e-BRIDGE ID-GATE – TWN3/4XX
- DATA OVERWRITE ENABLER – GP-1070
- IPsec ENABLER – GP-1080
- META SCAN ENABLER – GS-1010
- UNICODE FONT ENABLER – GS-1007
- ACCESSIBLE ARM – KK-2550
- DAMP HEATER – MF-5070E

¹⁾ Optional
²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

