


High Performance Yet Small Footprint

Compact, reliable and easy to share the ECOSYS P3150dn is the ideal high performance A4 mono printer for the busy workgroup. Its powerful controller, 50 pages per minute print speed and fast 5.4 second time to first print will make light work of large print volumes. KYOCERA's long life image drum technology, a high capacity toner and enhanced power management mean running costs and environmental footprint are kept to the minimum.

**ECOSYS P3150dn****A4 Monochrome printer****50 ppm for A4 and 74 ppm for A5****1200 x 1200 dpi resolution**

Specifications

GENERAL

KYOCERA ECOSYS Laser Monochrome Printer

Operation panel: 5 line LCD/LED display with back light with alphanumeric keypad

Engine speed (pages per minute): Up to 50 pages A4 in b/w. Duplex print speed: up to 35.5 page per minute A4

Resolution: 1,200 x 1,200 dpi

Warm-up time: Approx. 20 seconds or less from power on.

Time to first page: Approx. 5.4 sec. or less.

CPU: ARM Cortex-A9 Dual core 1.2GHz

(+ ARM Cortex-M3 100MHz)

Memory: Standard 512 MB RAM, max. 2,560 MB RAM

Standard interfaces: USB 2.0 (Hi-Speed USB), 2 x USB Host

Interfaces, Ethernet (10/100/1000Base), Slot for optional

internal print server or SSD hard disc, Slot for optional

SD / SDHC Card.

Integrated accounting: 100 department codes

Dimensions (W x D x H) – 380 mm x 410 mm x 320 mm,

388 mm x 410 mm x 343 mm incl. projections.

Weight: Main unit approx. 16.0 kg.

Approx. 16.6kg (with starter toner)

Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption

Print - mode: 636 Wh

Ready mode: 11 Wh

Sleep mode: 0.5 Wh

Noise (sound pressure level ISO 7779/

measurement distance of 1 meter)

Stand by mode: No measurable noise*

Printing: 54.5 dB(A) LpA. Quiet mode: 50.3 dB (A) LpA

Sleep mode: No measurable noise

Safety standards: GS, TÜV, CE; This unit is manufactured

according to ISO 9001 quality standard and ISO 14001

environmental standard. RoHS compatibility.

*in a standard office environment

PAPER HANDLING

All paper capacities quoted are based on paper thickness

of max. 0.11 mm. Please use paper recommended by

Kyocera under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray: MP tray:

60 - 220g/m², A4, A5, A6, Letter, Legal, Custom (70

x 140 - 216 x 356 mm), Banner paper up to 915 mm

500-sheet universal paper cassette: 60 - 120g/m² A4,

A6, Letter, Legal, Custom (105 x 148 - 216 x 356 mm)

Max. input capacity incl. options: 2,600 sheets

Duplex functionality as standard: A4, A5, B5, Letter, Legal,

Custom (140 x 210 mm - 216 x 356 mm), 60 - 120g/m²

Output capacity: 500-sheet- face-down with paper

full sensor, 250-sheets-face-up with PT-320.

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible),

PDF Direct Print, XPS Direct Print, TIFF/JPEG Direct Print

Support, Open XPS, Line Printer, IBM Proprinter X24E,

Epson LQ-850 with automatic emulation sensing.

Operating systems: All current Windows operating

systems, Mac OS X Version 10.9 or higher, UNIX LINUX,

as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL6/KPDL 3), 8 fonts

(Windows), 1 Bitmap font, 45 types of one-dimensional

barcodes, 1 type of two-dimensional barcode (PDF417)

Print features: PDF Direct Print, IPP printing,

e-mail printing, WSD print, secure printing via SSL,

IPsec, SNMPv3, Encrypted PDF Direct Print.

Mobile printing support: KYOCERA Mobile Print app for

iOS and Android; Mopria, Google Cloud

Print, Airprint, Direct Wi-Fi (opt).

CONSUMABLES

Average continuous toner yield in accordance with

ISO/IEC 17527. Starter toner is 8,000 pages, A4.

TK-3170 Toner Kit: Microfine toner for 15,500 pages, A4.

OPTIONS

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets,

60 - 120 g/m²; A4, A5, B5, Letter, Legal, Custom

(92 x 162 mm - 216 x 356 mm)

PF-3100 Bulk paper feeder and PB-325 Printer base: Max.

2,000 sheets, 60 - 220 g/m²; 76 x 148 - 216 x 305 mm, not

to be combined with PF-320

CB-360W Cabinet: Wooden desk with storage

capacity, Approx. 380 x 411 x 508 mm (WxDxH)

CB-365W Cabinet: Wooden desk with storage

capacity, Approx. 380 x 411 x 254 mm (WxDxH)

PT-320 Paper tray: 250-sheet-face-up output tray

Caster unit CA-3100

Memory upgrade: MD3-1024, MDDR3-2G, DDR3, 1GB/2GB

Storage Devices: HD-6 SSD hard disk: 32GB for

easy document management. HD-7 SSD hard disk:

128 GB for easy document management.

SECURITY

Data security kit (E): Encrypts data stored on optional SSD,

available when HD-6/7 is installed without any license

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available

Optional interface:

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT

(RJ45). IB-51: Wireless Lan (802.11b/g/n).

IB-36: Wireless Land (802.11b/g/n) with Wi-Fi Direct

IB-32B: IEEE1284 interface.

WARRANTY

1-year warranty as standard **. Kyocera guarantees

the drum and developer for 3 years or 500,000 pages

(whichever occurs sooner), provided each device is used

and cleaned in accordance with the service instructions.

KYOlife

Up to 5-year on-site warranty extensions

available for product and options.

ECOSYS stands for ECOlogy, ECONomy and SYSTEM printing. With long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership. The cartridge-free system means that you only need to add toner regularly. The modular design concept allows workflow enhancing functions. Integrated system software also provides crossnetwork compatibility.



KYOCERA Document Solutions Partner

MAY2019DSECOSSYP3150DN/VER1.0

KYOCERA Document Solutions UK
Eldon Court, 75-77 London Road, Reading, Berkshire. RG1 5BS
Tel +44 (0) 118 931 1500 – Fax +44 (0) 118 931 1108



kyoceradocumentsolutions.uk

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.